

RFID TRAINER is an excellent learning/training system for understanding basics, working and application of RFID (Radio Frequency Identification). It comprises of Contactless RFID Reader, 5 Mifare contactless cards, RFID Applications/Demo/Video Software. System works on 13.56 MHz and ISO 14443A read and write support. RFID is an automatic identification technique, storing and retrieving data using RFID tags or transponders. RFID tags (Active or Passive) is stuck into a product, animal or person for identifying using radiowaves. Most RFID tags have 2 parts: Integrated circuit for storing, processing information, modulating/demodulating a RF signal and Antenna for receiving/transmission. Applications for RFID includes transport payments, product tracking, animal identification, inventory systems, human implants, libraries etc.

Features:

- Software for understanding/working on Applications, Demo, Product Videos
- Contactless RFID Reader at 13.56 MHz with 6cm range
- Can be used for Active RFID tags (Optional)
- Read/Write ISO 14443A protocol Mifare 1K memory RFID cards
- 16 x 2 LCD Display with 89C51 Micro controller
- On board Breadboard with 840 tie points for designing other applications
- High Speed Transactions and flexible configurations
- USB to Serial interface for RFID Reader
- Parallel Interface for applications
- Weight: 6 Kg. (Approx.)
- Dimension: W 412 x H 150 x D310

Specifications:

- Operating Frequency: 13.56 Mhz
- Protocol: ISO 14443A and Mifare 1K Tags
- Antenna/Modulation: In built Antenna with ASK modulation
- Software:
 - Software for RFID Contact less card reader with 7 applications
 - Screen Shot Videos for 7 Applications in steps
 - Live Video Demo for the complete RFID training system
 - RFID Introduction
- Operating Range: Contact less 6 cm
- Voltage & Current: 5V@80mAfor Reader; 5V@200mAfor LCD; 12V@1.5Afor stepper motor
- Operating Temperature: -5 to 75 °C
- Applications
 - 1. Hardware Based Experiments
 - RFID Seven Segment Interface (Counter).
 - RFID Stepper Motor (Two) Interface. (With Two Stepper Motor)
 - RFID Logic Switch/LED Interface.
 - RFID LCD Interface.
 - RFID Breadboard Interface.
 - 2. Software Based Experiments
 - Alarm
 - Database
 - Calculator
 - Read/Write Block

Accessories:

•	Software CD4
•	Mains Cord1
•	25 Pin Parallel Male-Female Cable1
•	9 Pin Parallel Male-Female Cable1
•	Instruction Manual1
•	Patch Cord 2mm to 1mm 35cm Red & Black5 each.
•	Patch Cord 2mm to 1mm 15cm Red & Black5 each.

Mifare RFID cards -----5

Note: Specifications are subject to change.

Tesca Technologies Pvt. Ltd.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension, Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India, Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com

Website: www.tesca.in

