


Features:

- Thin, light, compact body design for one-hand operation
- 18mm triangular jaw allows for easy measurement on small cables
- Large, easy-to-read backlit display
- 200 A ac and dc current and 600 V ac and dc voltage measurement range
- 3000 Ω resistance range, continuity detection
- Zero function allows the display to be cleared for DC measurements
- Data Hold function
- CAT III 600 V safety rating

Specifications:

	Range	Resolution	Accuracy
AC current	200A	0.1A	2% \pm 5 digits (45-65Hz) 2.5% \pm 5 digits (65-400Hz)
DC current	200A	0.1A	2% \pm 5 digits
AC voltage	600 V	0.1 V	1.5% \pm 5 digits (45-400Hz)
DC voltage	600 V	0.1 V	1% \pm 5 digits
Resistance	300/3000 Ω	0.1/1 Ω	1% \pm 5 digits
Continuity	$\leq 70\Omega$		
General Specifications			
Size (LxWxH) mm	205 \times 60 \times 22		
Clamp opening	18 mm		
Weight	196 g		
Safety rating	CAT III 600 V		

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com