


**Description:**

With Optical plummet Having 1" least count and 2" accuracy, 30x Magnification along with all standard accessories:-

Standard Accessories Battery Charger (01 No.) Chargeable Battery (01 Nos.) Pencil Cell Battery (01 No.) Operation Manual (01 No.) Tool Kit (01 No.) Carrying Case (01 No.) Plum Bob (01 No.)

Aluminum Tripod (01 No.) Included

**Specifications :**

<b>Telescope</b>	Image	Positive
	Magnification Ratio	30×
	Effective Aperture of Object Lens	45mm
	Angle of View	1° 30'
	Shortest Visibility Distance	0.5m
	Stadia Multiplication Constant	100
	Stadia Addition Constant	0
	Resolution	3"
<b>Angle Measuring System</b>	Mode of Angle Measurement	Photoelectric Incremental Reading
	Min. Reading	1" 5" 10" Selectable
	Detection Method	H: Both Sides
		V: Single Side
	Precision of Angle Measurement	2"
	Unit of Angle	DEG MIL GON
Display	LCD Double Side	

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com

<b>Compensator</b>	Tilt Sensor	Automatic vertical compensation
		YES
	Range of Compensation	±3'
<b>Optical plummet</b>	Image	Positive
	Magnification Ratio	3×
	Angle of View	5°
	Focusing Range	0.5m~∞
<b>Sensitivity of vial</b>	tubular vial	30"/2mm
	circular vial	8'/2mm
<b>Ambient Temperature</b>		-20°C ~ +50°C
<b>Power Supply</b>	Battery	Rechargeable Ni-H Battery
	Source Voltage	6V
	Duration of Operation	16h
<b>Weight of Instrument</b>		5kg
<b>Dimensions</b>		164×154×340mm

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com