

**Specifications:-**

- Pace deviation bar graph.
- Automatic stress determination and display.
- Overload safely protection.
- Self aligning platen with fast accessory change capability.
- Configurable Engineering Unit for machine selection.
- Predefined Machine capacities for each engineering unit. Specific capacity can be selected from the drop down menu. Flexible Calibration Points. Calibration can be done on 5 to 10 points. Peak Load Peak Stress. Unique Record No. is displayed.
- EDI has provision to configure more than one Mode.
- Mode-4 runs with Mode-1 calibration.
- Dynamic Calibration
- Any Centronics dot matrix Printer.
- Menu Driven sample details.
- Data storage approx. 2000 records
- Data Download thru RS232 inASCII format. User can set break point.
- CVT supplied to ensure constant voltage to digital indicator.
- Easy to operate.
- Password protection for system & calibration setup.
- 2% overload facility to calibrate the machine upto full capacity.
- Start. Stop. Pause & Reset.
- Multifunction Keyboard

*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com