

Features

3½ Digital Multimeter with manual Range
Remote Control Testing
Live tester (Contact Type)



Technical Data :

Basic Functions	Range	Basic Accuracy
DC Voltage	200mV/2V/20V/200V/1000V	$\pm(1.2\% + 5)/\pm(1.5\% + 5)$
AC Voltage	200mV/2V/20V/200V/750V	$\pm(2\% + 5)/\pm(1.8\% + 5)/$ $\pm(1.5\% + 5)/\pm(2\% + 7)$
DC Current	2mA/200mA/20A	$\pm(1.5\% + 5)/\pm(2\% + 5)/$ $\pm(3\% + 5)$
AC Current	2mA/200mA/20A	$\pm(2\% + 5)/\pm(2.5\% + 5)/$ $\pm(3\% + 7)$
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ/200MΩ	$\pm(1.5\% + 5)/\pm(2\% + 5)/$ $\pm(5\% + 5) -10$
Capacitance	20nF/200nF/2uF/200uF	$\pm(3\% + 10)/\pm(5\% + 10)$

Special Function :

Diode test	✓	Input impedance	10MΩ
Transistor Testing	✓	Sampling Rate	3 times per second
Continuity Buzzer	Approx. < 50Ω	AC Frequency Response	40-400Hz
Auto Power OFF	Approx. 15 min.	Power	9V (6F22)

Standard Accessories : Test Leads, Holder, Manual
Dimension : 185(H) x 93(W) x 35(D) mm

Note: Specifications are subject to change.