

**Specifications:-**

- Network frequency: 0-400 Hz
- Mounting support: Plate, Rail, Under contactor
- Tripping threshold: 1.14 +/- 0.06 Ir conforming to IEC 60947-4-1
- Auxiliary contact composition: 1 NO + 1 NC
- [Ith] conventional free air thermal current: 5 A for signalling circuit
- Permissible current: 3 A at 120 V AC-15 for signalling circuit, 0.22 A at 125 V DC-13 for signalling circuit
- [Ue] rated operational voltage: 690 V AC 0...400 Hz for power circuit conforming to IEC 60947-4-1
- Associated fuse rating: 4 A gG for signalling circuit, 4 A BS for signalling circuit
- [Uimp] rated impulse withstand voltage: 6 kV
- Phase failure sensitivity: Tripping current 130 % of Ir on two phase, the last one at 0
- Control type:
 - 1) Red push-button: stop
 - 2) Blue push-button: reset
- Temperature compensation: -20...60 °C

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com