



Features:-

- 415 V Ac $\pm 10\%$, 50hz, 3 Phase 4 Wire
- Output Short Circuit By Cc Mode
- Separate Meters For Voltage And Current
- Set Voltage & Current By Coarse & Fine Potentiometers
- Leds To Indicate The Modes Of Operation Cc & Cv

Specifications:-

Input Power Supply	415 V AC $\pm 10\%$, 50Hz, 3 Phase 4 wire
Voltage Range	0 to 100V
Current Range	0 to 100A
Display	3½ digit 7 segment LED display for Voltage 3½ digit 7 segment LED display for Current
Load Regulation	$\pm 0.2\%$
Line Regulation	$\pm 0.2\%$
Ripple & Noise	$\pm 0.2\%$
Accuracy	$\pm 0.5\%$, ± 2 digit for Voltage & Current
Controls	Voltage and Current setting by Coarse & Fine potentiometer Power ON/OFF by MCB
Protection	Output short circuit by CC mode

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com