



Technical Specifications:-

Optional System: Single - Beam, Grating
Wavelength Range:190 - 1000nm
Bandwidth:1nm
Wavelength Accuracy: 0.5 nm
Wavelength Repeatability: 0.5nm
Wavelength Setting: Auto
Photometric Accuracy: ±0.005 Abs at 1.00 Abs
Photometric Repeatability: 0.1%T
Photometric Range: -0.3-3A,0-200%T
Stray Light :<0.3%T
Stability: 0.002A/h @500nm
Display: 128 * 64 Dots LCD, Alpha numeric
Detector: Solid state Silicon Photodiode
Measuring mode 1) Absorbance 2) % Transmittance 3) Concentration by K Factor and Multi standards
Absorbance range : -0.04 to 2.5 Abs
Standard Cell Holder:4-position 10mm cell changer
Light Source: Tungsten & Deuterium lamp
Output: USB port & Parallel port (printer)
Power Requirements: AC 85 ~ 250V
Dimension: 420x280x180mm
Weight: 2Kg

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com