



| SN. | Order Code | Description |
|-----|--------------|--------------------------|
| 01. | MT650 | 6 Holes-35 X 25 X 10 Cm |
| 02. | MT651 | 12 Holes-40 X 30 X 10 Cm |

Features:

- Industrial clinical laboratories
- Academic facilities
- Government research laboratories
- Environmental applications
- General Laboratory boiling application

Salient Features :

- Aesthetical exterior appearance
- Design simplicity and superior quality
- Easy cleaning and Maintenance free operation
- Fitted with drain plug

| Technical Specification | |
|--|--|
| Construction | Double walled |
| Outer Chamber | Fabricated from CRC Sheet, which is powder coated in attractive shades. |
| Inner chamber | 20 SWG Stainless Steel (AISI 304) ARGON WELDED |
| Insulation | Glass wool insulation |
| Chamber Size | 35 cm x 25 cm x 20 cm (W x D x H) |
| Chamber volume | 17.5 Liters |
| Temperature Range | 5 °C above ambient to 95 °C |
| Temperature Control | By Microprocessor based Auto Tune PID Digital Temperature Controller Cum Indicator |
| Temperature Display | LED Display |
| Temperature Accuracy | 0.1° C |
| Temperature Resolution | 0.1° C |
| Temperature Measurement | By Pt 100 sensor |
| Operation on | 220/230 volts AC single phase |
| Standard Accessories | Stainless steel lid with 06 holes of 3" diameter concentric rings, Power plug with cord wire |
| Overall Dimensions in Inches (L x W x H) | 24 X 14.5 X 11 (Only for 30650) |

Note: Specifications are subject to change.