

**Features:**

- Rugged Shielded case
- Other standard and custom HPF models
- Wide selection of cutoff frequency
- Small & Rigid design
- Economical

**Description:**


The TFL2206-3806SLC is a High pass filter in a shielded package fabricated using SMD LC technology. Covering DC-380 MHz bandwidth, these units offer decent matching within the passband and high rejection in stopband.


**Applications:**


- Amateur Radio Equipment's
- Test and measurement equipment
- Secure communications
- Walkie Talkie
- Radio Communications
- FM Applications

**Optional Accessories :**

- Adapter Kit
- 50 Ω Termination
- Directional coupler Kit
- Cable as per User Requirement (Figure-1)
- Antenna Kit



Electrical Specifications:	
Frequency Range	DC - 360 MHz
Power Capacity	0.5 W
Insertion Loss	- 3 dB Max
Return Loss	-15 dB Min
VSWR	1.5:1
Input Connector	SMA (M)/ SMA (F)
Output Connector	SMA (F)
Operating Temperature	0°C - 50°C
Mechanical Specifications:	
Dimensions (mm) :	 (L) = 56 (B) = 28.7 (H) = 17.4 (A) = 49 (∅) = 19
Shape:	Cuboidal/ Cylindrical shape
Weight :	Cuboidal :71 gm / Cylindrical :25 gm



**Filter Kits Available:**

- LPF ( 11 TYPES)
- HPF ( 9 TYPES)
- BPF ( 5 TYPES)



Note: Specifications are subject to change.